

Automatic Line Tester (HTS-3200-S)



SPECIFICATION

Parameter	Range	GO/ON-GO Limits
• Foreign Potential (AC/DC)	0-99 Volts	> 10 Volts NO-GO
• Insulation Resistance with respect to earth	0 - 2.5 Ohm (in Two range)	> 1 M Ohm GO
• Cross Insulation	0 - 2.5 M Ohm	> 1 M Ohm GO
• Line Capacitance	0 - 9.9 MFD	0.5 - 5.0 MFD GO
• Loop Resistance (With push button telephone)	0 - 2.5 Ohm	> 1200 Ohm - Go
• Dial Speed M-B Ratio	3-30 IPS 10-90%	9-11 IPS GO 60-72% GO
• New Line Tone	1000 Hx + 5%	
• Operating Voltage Ringing	AC 230 V 5%, 50 Hz, 5 watt, 75 Vrms, 50 Hz	
• Operating Temp Humidity	0-50 Degree C 20 - 80% w/o condensation	
• Weight Dimension	3 Kg. 22 (L) x 23 (W) x 11.5 (H) cms	
• Accessories	Pair of Test leads, Operation manual	

FEATURES

- Test automatically one by one all parameters of sub's line from MDF.

- Tests, Compares & then display's exact condition of the line by GO/ON-GO LED.
-

- Digital Display of
 - (a) Foreign Potential (AC/DC)
 - (b) Cross Insulation
 - (c) Leak of earth (A to E & B to E)
 - (d) Line Capacitance
 - (f) Loop Resistance
-

- Simultaneous Digital display of
 - (a) Dial Speed in IPS
 - (b) Dial ratio in %
 - (c) Digit Count
-

- New Line tone test
-

- GO/ON-GO TEST facility
-

- Tests all types of push button telephones both pulse and DTMF types
-

- Ring and Speech test
-

- Rugged Compact and Moulded ABS body
-

- Easy Operation and Minimal controls.
-