

Intelligent Line Tester With LCD Display (HTS-2001)



SPECIFICATION

- #### Automatic Test

It test a line completely even in the presence of foreign potnetial upto 10 volts.

- #### Testing Time

It test automatically one by one all line parameters within 10 seconds only.

- #### New Line Tone Test

It provides 800 c/s +/- 10% tone for both pair Identification.

- #### Display of results

It display results on 16 characters LCD display with built-in intelligence.

- #### Measurement range of Line Parameters

It test & displays on LCD extra value of

Foreign potential (AC/DC) upto 100 V

Cross Insulation upto 3 M ohms

Leak to earth upto 3 M ohms

Line capacitance upto 9.9 MFD

Loop resistance upto 3 K ohms

- #### Dial Test

It test & displays all the digits dialled from both tone & Pulse telephones

- #### Ring & Speech Test

It provide for ring & Speech test.

- #### Controls & Keys

Only soft keys areused to eliminate mechanical reatures.

- #### Ringing

75V rms, 50 Hz

•

Operating Voltage

AC 230 V+/- 5%, 50 Hz, 5 Watt

•

Weight

3 Kg. Approx

•

Dimensions

25 (L) x 26 (B) x 15 (H) cms

•

Accessories

Pair of test lead, operation manual

FEATURES

- Complete testing of Sub's Line & Telephone from MDF
 - It takes only 10 seconds to test a line even with foreign potential upto 10 volts & displays test results intelligently on LCD display.
 - It comes with one year free comprehensive maintenance
 - Ideally suitable for medium to large telephone exchanges
-